U3908


UI 39/8

External protection

8 VA - 70ºC/B

CE

Dual primary
Dual secondary



Weight/unit:
290 gr





Weight/minibox (Units: 1)
290 gr



Weight/bigbox (Units: 45)
13050 gr

HR Ref.	Primary		Sec.		Sec. In		V_o (In=0)	External protection Fuse	
	P1	P2	S1	S2	Is1	Is2		Sec. (F) S1|S2	Prim. (T) 115|230
U3908057	115 V	115 V	4.5 V	4.5 V	889 mA	889 mA	2x(6.5) V	2x(1000) mA	125|63 mA
U3908050	115 V	115 V	6 V	6 V	667 mA	667 mA	2x(8.7) V	2x(800) mA	125|63 mA
U3908051	115 V	115 V	7.5 V	7.5 V	533 mA	533 mA	2x(10.8) V	2x(630) mA	125|63 mA
U3908052	115 V	115 V	9 V	9 V	444 mA	444 mA	2x(13) V	2x(500) mA	125|63 mA
U3908053	115 V	115 V	12 V	12 V	333 mA	333 mA	2x(17.4) V	2x(400) mA	125|63 mA
U3908054	115 V	115 V	15 V	15 V	267 mA	267 mA	2x(21.7) V	2x(315) mA	125|63 mA
U3908055	115 V	115 V	18 V	18 V	222 mA	222 mA	2x(26.1) V	2x(250) mA	125|63 mA
U3908056	115 V	115 V	24 V	24 V	167 mA	167 mA	2x(34.8) V	2x(200) mA	125|63 mA





Technical characteristics:

- Designed and manufactured according regulations EN61558 EN60590 EN60472 UL506 UL1585
- Two-chamber coil
- Vacuum sealed
- Safety transformer class II / Protection index IP00 (For all models with no load voltage lower than 50V according to EN61558, and to 30V according to UL1585)
- External protection with fuse (See suggested type at table)
- Self-extinguishing plastic UL94-VO
- Epoxy resin class F
- Isolation: Prim./Sec. = 10 MOhm to 500 Vcc - Sec./Sec. = 2 MOhm to 500 Vcc
- Dielectric strength Prim. / Sec. = 5 kV / 1min.
- Secondary voltage tolerances 5%
- Test at 100% of all electrical parameters in production
- Reliability tests for production batch (life term)
- Certificates of production test results (under request)
- Certifications VDE, UL; others certifications under request: CSA, SEMKO