12W Multi-Plugs/Variable Power Supply

Rated Power: 12W

Input: 100-240V AC, 50 / 60Hz

Output: 3-12V

Dimension: 76*44*74mm

N.W.: 110g

Model:	YSV1000
Power:	12W max.
Input:	100-240VAC 50/60Hz
Output Voltage:	3V 4.5V 5V 6V 7.5V 9V 12VDC
Output Current:	1000mA
Input current:	0.5A max.
Inrush Current:	65 Amps max. at 230VAC/50Hz,full load
Leakage Current:	0.25mA Max. at 264VAC input
Energy Efficiency Level VI :	V
No Load Power Consumption ：	＜0.3W
Protections:	Short Circuit /Over Current /Over Voltage
Short Circuit Protection (SCP):	Protection to Zero Voltage
Over Voltage Protection (OVP):	≤Vout*150%
Over Current Protection (OCP):	110%-180%
Working TEMP.:	-20°C-50°C
Working Humidity:	5%-90% RH non-condensing
Storage TEMP.,Humidity and altitude:	-40℃ ~+70°C ambient temperature and a 5% to 95% relative humidity range throughout an altitude range of -60 meters to +5000 meters AMSL.
Input Plug:	EU,US,UK,AU etc. type according to customer's choice
Certificates and approvals:	UL,GS,CE,EMC,SAA,FCC,CB,PSE,CCC,RoHS,REACH
EMI EMISSION:	Radiation Test&Conduction Test: EN 55022/FCC Part 15 Harmonic Test : EN 61000-3-2 Flicker Test : EN 61000-3-3
EMS IMMUNITY:	ESD Test:EN 61000-4-2 RS Test:EN 61000-4-3 EFT Test:EN 61000-4-4

	Surge Test:EN 61000-4-5 CS Test:EN 61000-4-6 DIP Test:EN 61000-4-11
MTBF:	100000 hours minimum at full load at 25℃ ambient
Life:	3-5 years alternative
Dimension:	76*44*74mm
Weight:	110g
Packing:	20PCS/CTN,40*30*20cm